



- TOUCH-UP CAUTION -

If your building has been painted with a baked-on fluoropolymer finish it will resist color fade and chalking for an exceptionally long period of time. The touch up paint provided by Linetec is an air-dry acrylic enamel, which will exhibit chalking and fading characteristics at a much faster rate than that of your building. Therefore, it is recommended that touch-up paint be used as sparingly as possible, as any touch-up will become faded in contrast with the original building color after a few years

Regardless of the type of paint used on your original finish, please follow touch-up directions carefully for proper adhesion and final aesthetics in the coming years. This especially applies to the recommendation to use an artist's brush to apply the paint. Spray application is not recommended for touch-up paint. Applying the touch-up with a wide brush or other than a small artist's brush is not recommended.

Should there be a wide spandrel panel which has been pre-painted with a fluoropolymer finish which may require extensive touch up, air dry fluoropolymer systems are available, but need to be applied by a licensed fluoropolymer applicator. Should this be necessary, please call Linetec for a quote on our field repair services.

On any large-scale paint or touch-up application, we strongly suggest our Linetec Field Repair Department inspect the situation and determine the best suitable paint or repair procedure. Surface preparation, application, and finish should all be properly executed for a long lasting finish. A minor mistake in any segment of repair will cause major problems over time.

Linetec supplies air-dry finishes to aid our customers, in projects that were finished by Linetec, in minor situations. Under normal conditions we estimate that six (6) one-ounce bottles of aerosol touch-up should be sufficient for every 10,000 square feet of material which was painted at Linetec.

Because of the serious liabilities involved with field touch-up, Linetec prefers not to manufacture or sell air-dry products and will sell larger quantities only under the no liability clause as follows:

Linetec will not accept responsibility or liability for the touch-up paint, paint preparation, application, adhesion, or durability unless applied by our own field repair services. The purchasing customer will take full responsibility and liability for all aspects of touch-up other than those provided by Linetec's field repair services.

To manufacture touch-up paint, Linetec will require a signature from the purchasing customer, which indicates that they have read and understood the preceding paragraphs.

Please sign, date, and fill in the blanks for the relevant touch-up request. Fax request to 1-800-236-2589 or 715-843-4107.

Authorizing signature for touch-up paint _____

Date of Signature _____

P.O. # for touch-up paint: _____

Color to match paint on your job named: _____

To match (original manufacturer paint color & code #): _____

Project Name and Original PO # _____

Quantity Requested:

_____ Touch-up jars with brushes attached

_____ Spray cans

Linetec Field Service will be glad to prepare a quote for your repair. Contact your Sales Representative or call 715-843-4100.