



## USE OF TOUCH UP PAINT AUTHORIZATION FORM

Buildings painted with a high-performance PVDF paint coating will resist color fade and chalking for an exceptionally long period of time. Touch up paint, provided by Linetec or other applicators, are air-dry acrylic enamel paints which will exhibit chalking and fading characteristics at a much faster rate than factory applied coatings. Therefore, it is recommended that touch-up paint be used as sparingly as possible.

Please follow touch-up directions carefully for proper adhesion and appearance. This especially applies to the recommendation in using an artist's brush to apply the paint. Spray application is not recommended for touch-up paint. Applying the touch-up paint with a wide brush or anything other than a small artist's brush is not recommended.

For any repair other than a small scratch or blemish, we strongly suggest our Linetec field service department inspect the situation and determine the best suitable paint or repair procedure. Surface preparation, application, and finish should all be properly executed for a long lasting finish. A minor mistake in any segment of repair will cause major problems over time.

Linetec supplies air-dry touch-up paint to aid our customers in minor situations. Under normal conditions we estimate that one (1) two-ounce bottle of touch-up is sufficient for every 1,000 square feet of material painted at Linetec.

Because of the serious liabilities involved with field touch-up, Linetec prefers not to manufacture or sell touch-up products. With approval, based on factory painted project size, Linetec may sell very small quantities to our direct customer only under a no liability clause.

*Linetec will not accept responsibility or liability for the touch-up paint, paint preparation, application, adhesion, or durability unless applied by our own field repair services. The purchasing customer will take full responsibility and liability for all aspects of touch-up other than those provided by Linetec's field repair services.*

Any excessive use of touch-up voids the original finisher's warranty.

To manufacture touch-up paint, Linetec will require a signature from the purchasing customer, which indicates that they have read and understood the preceding paragraphs.



Please sign, date, and fill in the blanks for the relevant touch-up request.

Authorizing signature for touch-up paint: \_\_\_\_\_

Date of Signature: \_\_\_\_\_

P.O. # for touch-up paint: \_\_\_\_\_

Project name: \_\_\_\_\_

Paint Name and Code: \_\_\_\_\_

Quantity Requested:

\_\_\_\_\_ Touch-up jars with brushes attached

\_\_\_\_\_ Aerosol cans

Linetec Field Service will be glad to prepare a quote for your repair.

Contact your Sales Representative or our Field Service Manager at 715-846-3638.

Please send this fully completed form to your outside sales manager or to [sales@Linetec.com](mailto:sales@Linetec.com)